




REVISIONS		
Rev	DESCRIPTION	DATE
A	INITIAL RELEASE	2013.09.30



MATERIAL
Housing: High-impact Acrylonitrile Butadiene Styrene (ABS resin),
UL 94 V-0 rated
Shield: Stainless steel
Jack Housing: High-impact Polyethylene terephthalate (PBT resin),
UL 94 V-0 rated
Jack Contacts: Phosphor bronze round wire, $\varnothing=0.018$ in (0.46 mm),
plated with 0.76 μ in (30 μ m) thick hard gold over nickel underplate
PCB: FR4, UL 94 V-0 rated
RoHS 2 compliant

DIMENSIONS ARE IN[MM] TOLERANCES:					The information contained in this document is the sole property of Black Box Corporation of Pennsylvania. Any reproduction in part or whole without the written permission of Black Box Corp. is prohibited. ©Copyright 2012 Black Box Corporation of Pennsylvania d/b/a Black Box Network Services. All Rights Reserved.
-0.787" [20]	-1.969" [50]	-5.906" [150]	5.906" [150]	ANGLE	
± 0.008 " [0.2]	± 0.016 " [0.4]	± 0.020 " [0.5]	± 0.059 " [1.5]	$\pm 2^\circ$	
3rd Angle Projection					

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL \pm ANGULAR: MATCH \pm BEND \pm TWO PLACE DECIMAL \pm THREE PLACE DECIMAL \pm					
DRAWN		NAME	DATE	TITLE: RJ-45 Modular Splitter Shielded	
ENG APPR.		Kihai Lee	2013.09.30		
CHECKED		Jerry Su	2013.09.30	COMMENTS:	SIZE B
FINISH					DWG. NO. FM815-R2
DO NOT SCALE DRAWING					REV A
		SCALE: X		SHEET 1 OF 1	